

CASFLAM™ MGT UL/cUL

Style 5562
-60°C to +550 °C, 600V



Construction

Type: MGT wire

Core: nickel-coated copper (27%) (other conductor materials available)

Insulation: mica tape

Reinforcing braid: varnished fiberglass braid with high-temperature finish

Production

Range width: AWG 24 to 500kcmil

Options: Please consult us for any special requirements

Application

Household appliances: cabling for domestic or professional electrical appliances

Heating elements: cabling for heating resistors, cartridges, bands and plates

Other(s): cabling for furnaces, ovens, machines for thermoplastics and rubber, welding stations, ect.

General characteristics

Operating environment: good resistance to thermal shock

Chemical behavior: good resistance to oxidization

Thermal characteristics

Operating temperature: -60°C to +550 °C

Electrical characteristics

Operating Voltage: 600V

Approvals – Standards

“FT1 flame rating”: as per UL approval

UL approval: as per standard UL 758

Other approval: RoHS Compliant

Casmoc Part No.	Wire gauge (AWG)	Conductor structure			Wall thickness				Final O.D.		Approx. Wt.	
		# Strands	Diam. Of Strands		Mica Tape		Fiberglass Braid		(in)	(mm)	(lb./kft)	(kg/km)
			(in)	(mm)	(in)	(mm)	(in)	(mm)				
4210201	24	7	0.008	0.2	0.024	0.61	0.008	0.2	0.091	2.3	5	7.44
4210202	22	7	0.01	0.254	0.024	0.61	0.008	0.2	0.098	2.5	8	11.90
4210203	20	10	0.01	0.254	0.024	0.61	0.008	0.2	0.102	2.6	9	13.39
4210204	18	16	0.01	0.254	0.024	0.61	0.008	0.2	0.114	2.9	13	19.35
4210205	16	26	0.01	0.254	0.024	0.61	0.008	0.2	0.126	3.2	17	25.30
4210206	14	41	0.01	0.254	0.024	0.61	0.008	0.2	0.142	3.6	23	34.23
4210207	12	65	0.01	0.254	0.024	0.61	0.008	0.2	0.161	4.1	32	47.62
4210208	10	103	0.01	0.254	0.035	0.89	0.010	0.25	0.220	5.6	63	93.75
4210209	8	163	0.01	0.254	0.035	0.89	0.010	0.25	0.256	6.5	80	119.05
4210210	6	260	0.01	0.254	0.035	0.89	0.010	0.25	0.299	7.6	120	178.57
4210211	4	413	0.01	0.254	0.035	0.89	0.010	0.25	0.350	8.9	175	260.42
4210212	2	168	0.02	0.5	0.055	1.4	0.015	0.38	0.465	11.8	340	505.95
4210213	1	212	0.02	0.5	0.055	1.4	0.015	0.38	0.504	12.8	400	595.24
4210214	1/0	268	0.02	0.5	0.055	1.4	0.015	0.38	0.547	13.9	470	699.41
4210215	2/0	342	0.02	0.5	0.055	1.4	0.015	0.38	0.602	15.3	540	803.57
4210216	3/0	430	0.02	0.5	0.055	1.4	0.015	0.38	0.657	16.7	648	964.29
4210217	4/0	538	0.02	0.5	0.055	1.4	0.015	0.38	0.720	18.3	810	1205.36
4210218	250kcmil	633	0.02	0.5	0.060	1.52	0.015	0.38	0.776	19.7	1053	1566.97
4210219	300kcmil	760	0.02	0.5	0.060	1.52	0.015	0.38	0.839	21.3	1260	1875.01
4210220	350kcmil	886	0.02	0.5	0.060	1.52	0.015	0.38	0.894	22.7	1370	2038.70
4210221	400kcmil	396	0.031	0.8	0.060	1.52	0.015	0.38	0.945	24	1480	2202.39
4210222	500kcmil	495	0.031	0.8	0.060	1.52	0.015	0.38	1.039	26.4	1590	2366.08

COPYRIGHT

This document is protected under copyright law and is the property of Casmo Cable. Data contained herein is confidential to Casmo Cable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmo Cable or any affiliates without the prior written authorization of Casmo Cable

CAUTION

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmo Cable for dimensional verification, information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmo Cable is not responsible for any claim traceable to such error.

